Epson EB-L615U 000000 00000000 000000000 6000 ANSI 00000 3LCD WUXGA (1920x1200) 00000



Brand : Epson **Product code:** V11H901140

Product name: EB-L615U



Projector		Features	
Screen size compatibility * 1270 - 12700 mm (50 - 500") Projection distance 1.44 - 23.84 m Projection distance (wide) 1.4 - 14.8 m Projection distance (tele) 2.4 - 23.8 m Contrast ratio (dynamic) 2500000:1 Projector brightness * 6000 ANSI lumens Projection technology * 3LCD Projector native resolution * WUXGA (1920x1200) Contrast ratio (typical) * 2500000:1 Native aspect ratio * 16:10 Number of colours Projection technology * 16:10	1270 - 12700 mm (50 - 500")	Password protection	✓
		Multimedia	
		Built-in speaker(s) *	/
	2500000:1	RMS rated power	10 W
		Design	
	WUXGA (1920x1200) 2500000:1 16:10	Product type * Product colour * Placement Cable lock slot Cable lock slot type	Standard throw projector Black Desktop Kensington
Projector brightness (economic mode)	4200 ANSI lumens	Power	
Keystone correction, horizontal Keystone correction, vertical Matrix size	-30 - 30° -30 - 30° 1.7 cm (0.67")	Power consumption (typical) * Power consumption (standby) * Power consumption (economy	353 W 0.3 W 265 W
Light source		mode)	
Light source type *	Laser 20000 h 30000 h	AC input voltage AC input frequency	100-240 V 50 - 60 Hz
Service life of light source *		Software	30 00 112
Service life of light source (economic mode)		Software	
(CCOHOHIIC HIDGE)			VIA: AMX ('restron (Network)
Lens system		Software support	via: AMX, Crestron (Network), Control4, Extron
,	Manual	Software support Operational conditions	
Lens system	Manual 20 - 31.8 mm 1.5 - 1.7		
Lens system Focus * Focal length range Aperture range (F-F)	20 - 31.8 mm 1.5 - 1.7	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H)	-10 - 60 °C 20 - 80%
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability	20 - 31.8 mm 1.5 - 1.7	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-10 - 60 °C 20 - 80%
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range	20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1 -20 - 20%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range	20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1 -20 - 20%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video	20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth Package height	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm 208 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video Full HD *	20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm

Ports & interfaces		Packaging content	
USB 2.0 ports quantity	1	Quick start guide	✓
USB 2.0 Type-B ports quantity	1	Manual	✓
Audio (L/R) in *	1	Bundled software	EasyMP Monitor
Audio (L/R) out	1	Logistics data	
Serial interface type *	RS-232	•	1(-)
VGA (D-Sub) ports quantity *	3	Quantity per pack	1 pc(s)
HDMI ports quantity *	2	Products per pallet	14 pc(s)
Network		Pallet gross weight	0 g
		Pallet gross length	120 cm
Ethernet LAN *	✓	Pallet gross width	80 cm
Ethernet LAN (RJ-45) ports	1	Pallet gross height	2.18 m
Ethernet LAN data rates	10,100 Mbit/s	Products per pallet layer	2 pc(s)
Wi-Fi *	✓	Products per pallet layer (UK)	2 pc(s)
Wi-Fi standards	802.11a, 802.11b, 802.11g	Products per pallet (UK)	14 pc(s)
Miracast	✓	Pallet weight (UK)	0 g
Features		Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
Noise level (economic mode)	27 dB	Pallet height (UK)	2.18 m
Noise level * Country of origin	38 dB China	Other features	
		RS-232 ports	1



8715946661568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.