

TP-Link TL-PS110U Servidor d'impressió Ethernet LAN Blanc

Brand: TP-Link Product code: TL-PS110U V1

Product name: TL-PS110U

TL-PS110U - Servidor de impresión para el puerto USB, 1 puerto Fast Ethernet 10/100 Mbps RJ45 con auto-detección y apoya alerta de correo electrónico, Internet Printing Protocol (IPP) y SMB POST (Power On Self Test), registro del trabajo de impresión

TP-Link TL-PS110U. Color de producte: Blanc. Tipus de connexió a la xarxa: Ethernet LAN, Estàndard de xarxa: IEEE 802.3, IEEE 802.3u, Taxes de transferència de dades Ethernet LAN: 10,100 Mbit/s. Protocols de xarxa suportats: TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP, Gestió de protocols: Telnet. Sistemes operatius Windows suportats: Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows.... Certificació: FCC, CE



Features		Weight & dimensions	
Internal *	×	Height	30 mm
Product colour	White	Packaging data	
DHCP client	✓	Package type	Box
Network		Quantity per pack	1 pc(s)
Network connection type * Networking standards * Ethernet LAN data rates	Ethernet LAN IEEE 802.3, IEEE 802.3u 10,100 Mbit/s	Package width Package depth Package height	207 mm 168 mm 68 mm
Protocols		Package weight	280 g
	TCP/IP, IPX/SPX, NetBEUI, Apple	Operational conditions	
Supported network protocols * Management protocols Web-based management	Talk, LPR, IPP/SMB, RAW, TCP Telnet ✓	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T)	0 - 50 °C 0 - 70% -5 - 65 °C
Ports & interfaces		Other features	
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack	1 1	Data transfer rate Power requirements Dimensions (WxDxH)	100 Mbit/s 5V DC, 2A 73 x 65 x 30 mm
Software		Network ready	1
Windows operating systems supported	Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP	Compatible operating systems	Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later USB 2.0
Certificates		Non-operating relative humidity	0 - 80%
Certification	FCC, CE	(non-condensing)	0 - 00 /0
Weight & dimensions			
Width Depth	73 mm 65 mm		



6935364031008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.