



TP-Link TL-PS110U Druckserver Ethernet-LAN Weiß

Marke : TP-Link

Artikel-Code: TL-PS110U V1

Produktname : TL-PS110U



TL-PS110U - Print-Server für USB-Schnittstelle, 1 Fast-Ethernet-RJ45-Port mit 10/100Mbit/s und Auto-Sensing, unterstützt E-Mail Alert, Internet Printing Protocol (IPP) SMB und POST (Power On Self Test), print job log

TP-Link TL-PS110U. Produktfarbe: Weiß. Network Connection Typ: Ethernet-LAN, Netzstandard: IEEE 802.3, IEEE 802.3u, Ethernet LAN Datentransferraten: 10,100 Mbit/s. Unterstützte Netzwerkprotokolle: TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP, Management-Protokolle: Telnet. unterstützte Windows Betriebssysteme: Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows.... Zertifizierung: FCC, CE

Features		Weight & dimensions	
Internal *	✗	Height	30 mm
Product colour	White	Packaging data	
DHCP client	✓	Package type	Box
Network		Quantity per pack	1 pc(s)
Network connection type *	Ethernet LAN	Package width	207 mm
Networking standards *	IEEE 802.3, IEEE 802.3u	Package depth	168 mm
Ethernet LAN data rates	10,100 Mbit/s	Package height	68 mm
Protocols		Package weight	280 g
Supported network protocols *	TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP	Operational conditions	
Management protocols	Telnet	Operating temperature (T-T)	0 - 50 °C
Web-based management	✓	Operating relative humidity (H-H)	0 - 70%
Ports & interfaces		Storage temperature (T-T)	-5 - 65 °C
Ethernet LAN (RJ-45) ports *	1	Other features	
USB 2.0 ports quantity *	1	Data transfer rate	100 Mbit/s
DC-in jack	✓	Power requirements	5V DC, 2A
Software		Dimensions (WxDxH)	73 x 65 x 30 mm
Windows operating systems supported	Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP	Network ready	✓
Certificates		Compatible operating systems	Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later
Certification	FCC, CE	Interface	USB 2.0
Weight & dimensions		Non-operating relative humidity (non-condensing)	0 - 80%
Width	73 mm		
Depth	65 mm		



6935364031008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date