

Epson EB-L615U Standard throw projector 6000 ANSI lumens 3LCD WUXGA (1920x1200) Black



Brand : Epson

Product code: V11H901140

Product name : EB-L615U

3LCD, WLAN 802.11, Ethernet, Miracast, 6000lm, 16:10, 1920 x 1200, Zoom, 100 - 240V, 50/60Hz, 8.5kg

[Epson EB-L615U Standard throw projector 6000 ANSI lumens 3LCD WUXGA \(1920x1200\) Black:](#)

The EB-L615U is designed to replace existing lamp-based projectors in scenarios requiring 4,500-6,000-lumen solutions, and feature a compact, contemporary design that is smaller and lighter than other products of a similar brightness¹. The series offers a range of feature sets from basic entry-level models to more highly-specified units offering features such as HDBaseT connectivity, screen mirroring and lens shift so there is a model for every budget and specification.

| Projector | | Features | |
|--|--|-----------------------------------|--|
| Screen size compatibility * | 1270 - 12700 mm (50 - 500") | Password protection | ✓ |
| Projection distance | 1.44 - 23.84 m | Multimedia | |
| Projection distance (wide) | 1.4 - 14.8 m | Built-in speaker(s) * | ✓ |
| Projection distance (tele) | 2.4 - 23.8 m | RMS rated power | 10 W |
| Contrast ratio (dynamic) | 2500000:1 | Design | |
| Projector brightness * | 6000 ANSI lumens | Product type * | Standard throw projector |
| Projection technology * | 3LCD | Product colour * | Black |
| Projector native resolution * | WUXGA (1920x1200) | Placement | Desktop |
| Contrast ratio (typical) * | 2500000:1 | Cable lock slot | ✓ |
| Native aspect ratio * | 16:10 | Cable lock slot type | Kensington |
| Number of colours | 1.07 billion colours | Power | |
| Projector brightness (economic mode) | 4200 ANSI lumens | Power consumption (typical) * | 353 W |
| Keystone correction, horizontal | -30 - 30° | Power consumption (standby) * | 0.3 W |
| Keystone correction, vertical | -30 - 30° | Power consumption (economy mode) | 265 W |
| Matrix size | 1.7 cm (0.67") | AC input voltage | 100-240 V |
| Light source | | AC input frequency | 50 - 60 Hz |
| Light source type * | Laser | Software | |
| Service life of light source * | 20000 h | Software support | via: AMX, Crestron (Network), Control4, Extron |
| Service life of light source (economic mode) | 30000 h | Operational conditions | |
| Lens system | | Storage temperature (T-T) | -10 - 60 °C |
| Focus * | Manual | Operating relative humidity (H-H) | 20 - 80% |
| Focal length range | 20 - 31.8 mm | Storage relative humidity (H-H) | 10 - 90% |
| Aperture range (F-F) | 1.5 - 1.7 | Weight & dimensions | |
| Zoom capability | ✓ | Width | 440 mm |
| Zoom type | Manual | Depth | 304 mm |
| Zoom ratio | 1.6:1 | Height | 120 mm |
| Throw ratio | 1.35 - 2.2:1 | Weight * | 8.5 kg |
| Horizontal lens shift range | -20 - 20% | Package width | 538 mm |
| Vertical lens shift range | -50 - 50% | Package depth | 564 mm |
| Video | | Package height | 208 mm |
| Full HD * | ✓ | Package weight | 11.6 kg |
| Colour modes (2D) | Cinema, Dynamic | Packaging content | |
| Video colour modes | Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection | Remote control included * | ✓ |
| Ports & interfaces | | Cables included | AC, VGA |

| Ports & interfaces | | Packaging content | |
|-------------------------------|---------------------------|--------------------------------|----------------|
| USB 2.0 ports quantity | 1 | Quick start guide | ✓ |
| USB 2.0 Type-B ports quantity | 1 | Manual | ✓ |
| Audio (L/R) in * | 1 | Bundled software | EasyMP Monitor |
| Audio (L/R) out | 1 | | |
| Serial interface type * | RS-232 | Logistics data | |
| VGA (D-Sub) ports quantity * | 3 | Quantity per pack | 1 pc(s) |
| HDMI ports quantity * | 2 | Products per pallet | 14 pc(s) |
| Network | | Pallet gross weight | 0 g |
| Ethernet LAN * | ✓ | Pallet gross length | 120 cm |
| Ethernet LAN (RJ-45) ports | 1 | Pallet gross width | 80 cm |
| Ethernet LAN data rates | 10,100 Mbit/s | Pallet gross height | 2.18 m |
| Wi-Fi * | ✓ | Products per pallet layer | 2 pc(s) |
| Wi-Fi standards | 802.11a, 802.11b, 802.11g | Products per pallet layer (UK) | 2 pc(s) |
| Miracast | ✓ | Products per pallet (UK) | 14 pc(s) |
| Features | | Pallet weight (UK) | 0 g |
| Noise level (economic mode) | 27 dB | Pallet length (UK) | 120 cm |
| Noise level * | 38 dB | Pallet width (UK) | 100 cm |
| Country of origin | China | Pallet height (UK) | 2.18 m |
| | | Other features | |
| | | RS-232 ports | 1 |



8715946661568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-APR-2025. Prints or copies of Information are only valid on the printed Publication date