

## Samsung SCX-6345NJ + JScribe Laser A4 1200 x 1200 DPI 41 ppm

**Brand :** Samsung

**Product code:** SCX6345NJ

**Product name :** SCX-6345NJ + JScribe

SCX-6345NJ - 1200 x 1200 dpi, 41 ppm, A4, laser, fax, LCD, 256MB, USB 2.0, Ethernet + JScribe

[Samsung SCX-6345NJ + JScribe Laser A4 1200 x 1200 DPI 41 ppm:](#)

Take a look at this one-stop digital solution that can manage your entire printing workflow. An MFP copier that can match the output of large contract-base A3 copiers and can also scan, print and fax. Add in high performance features like duplex, high capacity paper trays and simple one touch operations and you have a solution capable of the highest workflow demands. With Samsung SCX-6345N it's not that hard to imagine.

Samsung SCX-6345NJ + JScribe. Print technology: Laser, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning. Faxing: Mono faxing. Maximum ISO A-series paper size: A4



| Printing  |                        | Paper handling                        |   |
|---|------------------------|---------------------------------------|---|
| Print technology *                                  | Laser                  | Maximum ISO A-series paper size *     | A4  |
| Printing *  | ✗                      | Paper tray media types *              | Bond paper, Card stock, Envelopes, Recycled paper, Transparencies |
| Duplex printing *                                   | ✓                      | ISO A-series sizes (A0...A9) *        | A4, A5, A6  |
| Maximum resolution *                                | 1200 x 1200 DPI        | ISO B-series sizes (B0...B9)          | B5  |
| Print speed (black, normal quality, A4/US Letter) * | 41 ppm                 | Non-ISO print media sizes             | Folio, Statement  |
| Warm-up time  | 35 s                   | JIS B-series sizes (B0...B9)          | B5  |
| Time to first page (black, normal)                  | 8 s                    | Envelopes sizes                       | B5, C5, C6, DL  |
| Copying   |                        | Ports & interfaces                    |   |
| Copying *   | Mono copying           | Standard interfaces                   | USB 2.0   |
| Maximum copy resolution *                           | 600 x 600 DPI          | USB port                              | ✓   |
| Copy speed (black, normal quality, A4)              | 43 cpm                 | USB 2.0 ports quantity                | 1   |
| Maximum number of copies                            | 999 copies             | Network                               |   |
| Copier resize                                       | 25 - 400%              | Ethernet LAN *                        | ✓   |
| Scanning  |                        | Performance                           |   |
| Scanning *  | Colour scanning        | Internal memory *                     | 256 MB  |
| Maximum scan resolution                             | 4800 x 4800 DPI        | Sound pressure level (printing)       | 60 dB   |
| Scanner type *                                      | Flatbed scanner        | Sound power level (standby)           | 43 dB   |
| Scan technology                                     | CCD                    | Mac compatibility                     | ✓   |
| Scan to   | FTP                    | Design                                |   |
| Greyscale levels                                    | 256                    | Market positioning *                  | Business  |
| Fax   |                        | Built-in display *                    | ✓   |
| Faxing *  | Mono faxing            | Display                               | LCD   |
| Modem speed   | 33.6 Kbit/s            | Power                                 |   |
| Fax memory  | 16 MB                  | Power consumption (average operating) | 900 W   |
| Fax speed dialing (max numbers)                     | 200                    | Power consumption (PowerSave)         | 35 W  |
| Fax speed (A4)                                      | 3 sec/page             | Power consumption (standby)           | 170 W   |
| Features  |                        | Operational conditions                |   |
| Maximum duty cycle *                                | 200000 pages per month | Operating relative humidity (H-H)     | 20 - 80%  |
| Digital sender                                      | ✗                      | Operating temperature (T-T)           | 10 - 32 °C  |
| Input & output capacity                             |                        | Weight & dimensions                   |   |
| Total output capacity *                             | 500 sheets             | Weight                                | 44.5 kg   |
| Multi-Purpose tray                                  | ✓                      | Other features                        |   |
| Multi-Purpose tray input capacity                   | 100 sheets             | Dimensions (WxDxH)                    | 637.4 x 489 x 616 mm  |
| Auto document feeder (ADF)                          | ✓                      | Network ready                         | ✓   |
| Auto document feeder (ADF) input capacity           | 50 sheets              |                                       |   |

| Input & output capacity |            | Other features               |  |
|-------------------------|------------|------------------------------|--|
| Maximum input capacity  | 520 sheets |                              | Windows<br>98/Me/NT4.0/2000/XP/2003 Linux<br>OS (Red Hat 8-9, Fedora Core 1-4,<br>Mandrake 9.2-10.1, SuSE 8.2-9.2)<br>Mac OS 8.6-9.2/10.1-10.4 |
|                         |            | Compatible operating systems |  |
|                         |            | Emulations                   | PCL6, PostScript 3   |
|                         |            | All-in-one functions         | Copy, Fax, Scan  |
|                         |            | Colour all-in-one functions  | Scan, No   |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2025. Prints or copies of Information are only valid on the printed Publication date