

## DELL PowerEdge T360 server 2 TB Tower (4.5U) Intel Xeon E E-2478 2.8 GHz 16 GB DDR5-SDRAM 600 W

Brand : DELL Product family: PowerEdge Product code: T360-FY25Q3

**Product name:** T360

DELL PowerEdge T360. Processor family: Intel Xeon E, Processor frequency: 2.8 GHz, Processor: E-2478. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 2 TB, Hard drive size: 3.5", Hard drive interface: SATA III. Ethernet LAN connection, Cabling technology: 10/100/1000Base-T(X). Power supply: 600 W, Redundant power supply (RPS) support. Chassis type: Tower (4.5U)





| Processor                                   |                           | Design                                       |   |
|---|---------------------------|--|---|
| Processor manufacturer *                    | Intel                     | Product colour                               | Black   |
| Processor family *                          | Intel Xeon E              | Performance                                  |   |
| Processor model *                           | E-2478                    | Remote administration                        | iDRAC9, Basic 16G   |
| Processor frequency *                       | 2.8 GHz<br>5.2 GHz        | Software                                     |   |
| Processor boost frequency Performance cores | 5.2 GHZ<br>8              |  | ~   |
| Processor cores                             | 8                         | Operating system installed *                 | X   |
| Processor cache                             | 24 MB                     |  | Canonical Ubuntu Server LTS Microsoft Windows Server with |
| Number of processors installed              | 1                         | Compatible operating systems *               | Hyper-V Red Hat Enterprise Linux                          |
| Thermal Design Power (TDP)                  | 80 W                      |  | SUSE Linux Enterprise Server<br>VMware ESXi               |
| Processor threads                           | 16                        | Power  | 77.110.0 257.1  |
| Memory types supported by                   | DDR5-SDRAM                |  |   |
| processor                                   | DDIG SDIAM                | Redundant power supply (RPS) support *       | ✓   |
| Memory clock speeds supported by processor  | 4800 MHz                  | Power supply *                               | 600 W   |
| Memory                                      |                           | Number of redundant power supplies supported | 2   |
| Internal memory * Internal memory type *    | 16 GB<br>DDR5-SDRAM       | Number of redundant power supplies installed | 2   |
| Buffered memory type                        | Unregistered (unbuffered) | Power supply input voltage                   | 125 V   |
| Memory slots                                | 4x DIMM                   | Power cable length                           | 3 m   |
| ECC   | <b>✓</b>                  | Power cable connector 1                      | C13 coupler   |
| Memory data transfer rate                   | 4800 MT/s                 | Power cable current                          | 15 A  |
| Maximum internal memory *                   | 128 GB                    | Operational conditions                       |   |
| Storage                                     |                           | Storage temperature (T-T)                    | -40 - 65 °C   |
| Total storage capacity *                    | 2 TB                      | Storage relative humidity (H-H)              | 5 - 95%   |
| Number of HDDs installed                    | 1                         | Operating altitude                           | 0 - 2048 m  |
| HDD capacity                                | 2 TB                      | Non-operating altitude                       | 0 - 12000 m   |
| HDD interface                               | SATA III                  |  |   |

| Storage  |                                   | Carbon footprint  |                      |
|--|-----------------------------------|---|----------------------|
| HDD speed  | 7200 RPM                          | Total carbon footprint (kg of CO2e)                     | 1409                 |
| HDD size   | 3.5"                              | Total carbon emissions, standard deviation (kg of CO2e) | 1213                 |
| RAID support * Supported RAID controllers Hot-Plug support | PERC H755                         | Carbon emissions, manufacturing (kg of CO2e)            | 296                  |
| Optical drive type *                                       | X                                 | Carbon emissions, logistics (kg of CO2e)                | 155                  |
| Internal drive bays  | 8                                 | Carbon emissions, energy usage (kg of CO2e)             | 930                  |
| Network  | Broadcom 5720, Intel I210, Intel® | Carbon emissions, end-of-life (kg of CO2e)              | 28                   |
| LAN controller  Ethernet LAN                               | X722                              | Total carbon emissions, w/o use phase (kg of CO2e)      | 479                  |
| Cabling technology   | 10/100/1000Base-T(X)              | PAIA version  | 1.4.0, 2024          |
| Ethernet interface type                                    | Gigabit Ethernet                  | Weight & dimensions                                     |                      |
| Ports & interfaces   |                                   | Width   | 175 mm               |
| Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity        | 2<br>5                            | Depth<br>Height   | 581.1 mm<br>369.5 mm |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A                           | 2                                 | Technical details                                       |                      |
| ports quantity VGA (D-Sub) ports quantity                  | 1                                 | Supported storage drives form factor (internal)         | 3.5"                 |
| Serial ports quantity                                      | 1                                 | Other features  |                      |
| Expansion slots  |                                   | Data transfer rate                                      | 6 Gbit/s             |
| PCI Express x4 slots                                       | 2                                 | Bytes per sector  | 512n                 |
| Design   |                                   |   |                      |
| Chassis type *   | Tower (4.5U)                      |   |                      |





884116466369

0884116466369

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.