



TP-Link TL-PS110U servidor de impresión LAN Ethernet Blanco

Marca : TP-Link

Código del producto: TL-PS110U V1

Nombre del producto : TL-PS110U



TP-Link TL-PS110U. Color del producto: Blanco. Tipo de conexión de red: LAN Ethernet, Estándares de red: IEEE 802.3, IEEE 802.3u, Ethernet LAN, velocidad de transferencia de datos: 10,100 Mbit/s. Protocolos de red compatibles: TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP, Protocolos de gestión: Telnet. Sistemas operativos Windows soportados: Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows.... Certificación: FCC, CE

| Features | | Weight & dimensions | |
|-------------------------------------|--|--|---|
| Internal * | ✗ | Height | 30 mm |
| Product colour | White | Packaging data | |
| DHCP client | ✓ | Package type | Box |
| Network | | Quantity per pack | 1 pc(s) |
| Network connection type * | Ethernet LAN | Package width | 207 mm |
| Networking standards * | IEEE 802.3, IEEE 802.3u | Package depth | 168 mm |
| Ethernet LAN data rates | 10,100 Mbit/s | Package height | 68 mm |
| Protocols | | Package weight | 280 g |
| Supported network protocols * | TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP | Operational conditions | |
| Management protocols | Telnet | Operating temperature (T-T) | 0 - 50 °C |
| Web-based management | ✓ | Operating relative humidity (H-H) | 0 - 70% |
| Ports & interfaces | | Storage temperature (T-T) | -5 - 65 °C |
| Ethernet LAN (RJ-45) ports * | 1 | Other features | |
| USB 2.0 ports quantity * | 1 | Data transfer rate | 100 Mbit/s |
| DC-in jack | ✓ | Power requirements | 5V DC, 2A |
| Software | | Dimensions (WxDxH) | 73 x 65 x 30 mm |
| Windows operating systems supported | Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP | Network ready | ✓ |
| Certificates | | Compatible operating systems | Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later |
| Certification | FCC, CE | Interface | USB 2.0 |
| Weight & dimensions | | Non-operating relative humidity (non-condensing) | 0 - 80% |
| Width | 73 mm | | |
| Depth | 65 mm | | |



6935364031008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date