## **TP-Link TL-PS110U nyomtatószerver Ethernet LAN Fehér**

Márka : TP-Link


Termék kód: TL-PS110U V1

Termék neve : TL-PS110U

TP-Link TL-PS110U. Termék színe: Fehér. Hálózati csatlakozás típusa: Ethernet LAN, Hálózati szabvány: IEEE 802.3, IEEE 802.3u, Ethernet LAN adatátviteli sebességek: 10,100 Mbit/s. Támogatott hálózati protokollok: TCP/IP, IPX/SPX, NetBEUI, Apple Talk, LPR, IPP/SMB, RAW, TCP, Igazgatási protokollok: Telnet. Támogatott Windows operációs rendszerek: Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows.... Tanúsítványok: FCC, CE



Features		Weight & dimensions	
Internal *	×	Height	30 mm
Product colour	White	Packaging data	
DHCP client	1	Package type	Box
Network		Quantity per pack	1 pc(s)
Network connection type *	Ethernet LAN	Package width	207 mm
Networking standards *	IEEE 802.3, IEEE 802.3u	Package depth	168 mm
Ethernet LAN data rates	10,100 Mbit/s	Package height Package weight	68 mm 280 g
Protocols		5 5	280 y
Supported network protocols *	TCP/IP, IPX/SPX, NetBEUI, Apple	Operational conditions	
	Talk, LPR, IPP/SMB, RAW, TCP	Operating temperature (T-T)	0 - 50 °C
Management protocols	Telnet	Operating relative humidity (H-H)	0 - 70%
Web-based management	1	Storage temperature (T-T)	-5 - 65 °C
Ports & interfaces		Other features	
i orts a interfaces			
Ethernet LAN (RJ-45) ports *	1	Data transfer rate	100 Mbit/s
	1 1	Data transfer rate Power requirements	5V DC, 2A
Ethernet LAN (RJ-45) ports *		Data transfer rate Power requirements Dimensions (WxDxH)	5V DC, 2A 73 x 65 x 30 mm
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity *	1	Data transfer rate Power requirements	5V DC, 2A 73 x 65 x 30 mm ✔
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT,	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack <b>Software</b> Windows operating systems supported	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems Interface	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack Software Windows operating systems supported Certificates	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack Software Windows operating systems supported Certificates Certification	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT,	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems Interface Non-operating relative humidity	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later USB 2.0
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack Software Windows operating systems supported Certificates	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems Interface Non-operating relative humidity	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later USB 2.0
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity * DC-in jack Software Windows operating systems supported Certificates Certification	1 ✓ Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows ME, Windows NT, Windows Vista, Windows XP	Data transfer rate Power requirements Dimensions (WxDxH) Network ready Compatible operating systems Interface Non-operating relative humidity	5V DC, 2A 73 x 65 x 30 mm ✓ Windows 9x/ME, Windows NT/2000/XP/Vista, Mac OS 8.1 or Later, UNIX/Linux, Netware 3.12 or Later USB 2.0



6935364031008

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.