Epson EB-L615U Proyektor lempar standar 6000 ANSI lumen 3LCD WUXGA (1920x1200) Hitam

EPSON __

Brand : Epson **Product code:** V11H901140


Product name: EB-L615U

Epson EB-L615U. Kecerahan proyektor: 6000 ANSI lumen, Teknologi proyeksi: 3LCD, Resolusi asli proyektor: WUXGA (1920x1200). Tipe sumber cahaya: Laser, Masa penggunaan sumber cahaya: 20000 j, Masa penggunaan sumber cahaya (mode hemat): 30000 j. Fokus: Pedoman, Jangkauan panjang fokus: 20 - 31.8 mm, Rentang bukaan (F-F): 1,5 - 1,7. Mode warna (2D): Bioskop, Dinamis, Mode warna video: Bioskop, Dinamis, Presentasi, sRGB, Mode simulasi DICOM, Multi-projection. Tipe antarmuka serial: RS-232



Projector		Features	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Password protection	✓
Projection distance	1.44 - 23.84 m	Multimedia	
Projection distance (wide) Projection distance (tele)	1.4 - 14.8 m 2.4 - 23.8 m	Built-in speaker(s) *	✓
Contrast ratio (dynamic)	2500000:1	RMS rated power	10 W
Projector brightness *	6000 ANSI lumens 3LCD	Design	
Projection technology *		Product type *	Standard throw projector
Projector native resolution *	WUXGA (1920x1200)	Product colour *	Black
Contrast ratio (typical) *	2500000:1	Placement	Desktop
Native aspect ratio *	16:10	Cable lock slot	√
Number of colours	1.07 billion colours	Cable lock slot type	Kensington
Projector brightness (economic mode)	4200 ANSI lumens	Power	
Keystone correction, horizontal	-30 - 30°	Power consumption (typical) *	353 W
Keystone correction, vertical	-30 - 30°	Power consumption (standby) *	0.3 W
Matrix size	1.7 cm (0.67")	Power consumption (economy	265 W
Light source		mode) AC input voltage	100-240 V
Light source type *	Laser	AC input frequency	50 - 60 Hz
Service life of light source *	20000 h	Software	
Service life of light source	30000 h	Joitwale	
(economic mode)	3000011		via: AMY Crestron (Network)
(111)	3000011	Software support	via: AMX, Crestron (Network), Control4, Extron
(economic mode) Lens system Focus *	Manual	Software support Operational conditions	, , , , , , , , , , , , , , , , , , , ,
Lens system			, , , , , , , , , , , , , , , , , , , ,
Lens system Focus *	Manual	Operational conditions	Control4, Extron
Lens system Focus * Focal length range	Manual 20 - 31.8 mm	Operational conditions Storage temperature (T-T)	Control4, Extron
Lens system Focus * Focal length range Aperture range (F-F)	Manual 20 - 31.8 mm 1.5 - 1.7	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H)	-10 - 60 °C 20 - 80%
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-10 - 60 °C 20 - 80%
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio	Manual 20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	-10 - 60 °C 20 - 80% 10 - 90%
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio	Manual 20 - 31.8 mm 1.5 - 1.7 Manual 1.6:1 1.35 - 2.2:1	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50%	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth Package height	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm 208 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video Full HD * Colour modes (2D)	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50% ✓ Cinema, Dynamic Cinema, Dynamic, Presentation,	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth Package height Package weight	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video Full HD *	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50% ✓ Cinema, Dynamic	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth Package height	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm 208 mm
Lens system Focus * Focal length range Aperture range (F-F) Zoom capability Zoom type Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Video Full HD * Colour modes (2D)	Manual 20 - 31.8 mm 1.5 - 1.7 ✓ Manual 1.6:1 1.35 - 2.2:1 -20 - 20% -50 - 50% ✓ Cinema, Dynamic Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode,	Operational conditions Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight * Package width Package depth Package height Package weight	Control4, Extron -10 - 60 °C 20 - 80% 10 - 90% 440 mm 304 mm 120 mm 8.5 kg 538 mm 564 mm 208 mm

Ports & interfaces		Packaging content	
USB 2.0 ports quantity	1	Quick start guide	✓
USB 2.0 Type-B ports quantity	1	Manual	✓
Audio (L/R) in *	1	Bundled software	EasyMP Monitor
Audio (L/R) out	1	Logistics data	
Serial interface type *	RS-232	•	1(-)
VGA (D-Sub) ports quantity *	3	Quantity per pack	1 pc(s)
HDMI ports quantity *	2	Products per pallet	14 pc(s)
Network		Pallet gross weight	0 g
		Pallet gross length	120 cm
Ethernet LAN *	✓	Pallet gross width	80 cm
Ethernet LAN (RJ-45) ports	1	Pallet gross height	2.18 m
Ethernet LAN data rates	10,100 Mbit/s	Products per pallet layer	2 pc(s)
Wi-Fi *	✓	Products per pallet layer (UK)	2 pc(s)
Wi-Fi standards	802.11a, 802.11b, 802.11g	Products per pallet (UK)	14 pc(s)
Miracast	✓	Pallet weight (UK)	0 g
Features		Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
Noise level (economic mode)	27 dB	Pallet height (UK)	2.18 m
Noise level * Country of origin	38 dB China	Other features	
		RS-232 ports	1



8715946661568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.