Epson EB-L615U 6000 ANSI 3LCD WUXGA (1920x1200)

**** : Epson

: V11H901140

**** : EB-L615U

Epson EB-L615U. (): 6000 ANSI , (): 3LCD, (): WUXGA (1920x1200). : , : 20000 , (): 30000 . : , : 20 - 31.8 mm, (F-F): 1.5 - 1.7. (2D): , . : , , (), sRGB, DICOM(), Multi-projection. (): RS-232

Projector	
Screen size compatibility *	1270 - 12700 mm (50 - 500")
Projection distance	1.44 - 23.84 m
Projection distance (wide)	1.4 - 14.8 m
Projection distance (tele)	2.4 - 23.8 m
Contrast ratio (dynamic)	2500000:1
Projector brightness *	6000 ANSI lumens
Projection technology *	3LCD
Projector native resolution *	WUXGA (1920x1200)
Contrast ratio (typical) *	2500000:1
Native aspect ratio *	16:10
Number of colours	1.07 billion colours
Projector brightness (economic mode)	4200 ANSI lumens
Keystone correction, horizontal	-30 - 30°
Keystone correction, vertical	-30 - 30°
Matrix size	1.7 cm (0.67")

Light source	
Light source type *	Laser
Service life of light source *	20000 h
Service life of light source (economic mode)	30000 h

Lens system	
Focus *	Manual
Focal length range	20 - 31.8 mm
Aperture range (F-F)	1.5 - 1.7
Zoom capability	✔
Zoom type	Manual
Zoom ratio	1.6:1
Throw ratio	1.35 - 2.2:1
Horizontal lens shift range	-20 - 20%
Vertical lens shift range	-50 - 50%

Video	
Full HD *	✔
Colour modes (2D)	Cinema, Dynamic
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection

Ports & interfaces

Features	
Password protection	✔

Multimedia	
Built-in speaker(s) *	✔
RMS rated power	10 W

Design	
Product type *	Standard throw projector
Product colour *	Black
Placement	Desktop
Cable lock slot	✔
Cable lock slot type	Kensington

Power	
Power consumption (typical) *	353 W
Power consumption (standby) *	0.3 W
Power consumption (economy mode)	265 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz

Software	
Software support	via: AMX, Crestron (Network), Control4, Extron

Operational conditions	
Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions	
Width	440 mm
Depth	304 mm
Height	120 mm
Weight *	8.5 kg
Package width	538 mm
Package depth	564 mm
Package height	208 mm
Package weight	11.6 kg

Packaging content	
Remote control included *	✔
Cables included	AC, VGA

Ports & interfaces

USB 2.0 ports quantity	1
USB 2.0 Type-B ports quantity	1
Audio (L/R) in *	1
Audio (L/R) out	1
Serial interface type *	RS-232
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	2

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100 Mbit/s
Wi-Fi *	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g
Miracast	✔

Features

Noise level (economic mode)	27 dB
Noise level *	38 dB
Country of origin	China

Packaging content

Quick start guide	✔
Manual	✔
Bundled software	EasyMP Monitor

Logistics data

Quantity per pack	1 pc(s)
Products per pallet	14 pc(s)
Pallet gross weight	0 g
Pallet gross length	120 cm
Pallet gross width	80 cm
Pallet gross height	2.18 m
Products per pallet layer	2 pc(s)
Products per pallet layer (UK)	2 pc(s)
Products per pallet (UK)	14 pc(s)
Pallet weight (UK)	0 g
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	2.18 m

Other features

RS-232 ports	1

8715946661568