## Epson EB-L615U Projetor de distância normal 6000 ANSI lumens 3LCD WUXGA (1920x1200) Preto

Marca : Epson

Código do produto: V11H901140

Nome do produto : EB-L615U

Epson EB-L615U. Luminosidade do projector: 6000 ANSI lumens, Tecnologia da projecção: 3LCD, Resolução nativa do projetor: WUXGA (1920x1200). Tipo de fonte de luz: Laser, Vida útil da fonte de luz: 20000 h, Vida útil da fonte de luz (modo económico): 30000 h. Foco: Manual, Comprimento focal: 20 -31.8 mm, Amplitude de abertura (F-F): 1,5 - 1,7. Modos de cor (2D): Cinema, Dinâmica, Modos de cor de vídeo: Cinema, Dinâmica, Apresentação, sRGB, Modo de simulação DICOM, Multi-projection. Tipo de interface em série: RS-232





Projector		Features	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Password protection	1
Projection distance 1	1.44 - 23.84 m	Multimedia	
Projection distance (wide)	1.4 - 14.8 m	Built-in speaker(s) *	1
Projection distance (tele)	2.4 - 23.8 m	RMS rated power	10 W
Contrast ratio (dynamic) Projector brightness *	2500000:1 6000 ANSI lumens 3LCD	•	10 W
		Design	
Projection technology * Projector native resolution *	WUXGA (1920x1200)	Product type *	Standard throw projector
Contrast ratio (typical) *	2500000:1	Product colour *	Black
Native aspect ratio *	16:10	Placement	Desktop
Number of colours	1.07 billion colours	Cable lock slot	
Projector brightness (economic	4200 ANSI lumens	Cable lock slot type	Kensington
mode)		Power	
Keystone correction, horizontal	-30 - 30°	Power consumption (typical) *	353 W
Keystone correction, vertical	-30 - 30°	Power consumption (standby) *	0.3 W
Matrix size	1.7 cm (0.67")	Power consumption (economy mode)	265 W
Light source		AC input voltage	100-240 V
Light source type *	Laser	AC input frequency	50 - 60 Hz
Service life of light source *	20000 h	Software	
Service life of light source (economic mode)	30000 h	Solution	via: AMX, Crestron (Network),
Lens system		Software support	Control4, Extron
Focus *	Manual	Operational conditions	
Focal length range	20 - 31.8 mm	Storage temperature (T-T)	-10 - 60 °C
Aperture range (F-F)	1.5 - 1.7	Operating relative humidity (H-H)	20 - 80%
Zoom capability	1	Storage relative humidity (H-H)	10 - 90%
Zoom type	Manual	Weight & dimensions	
Zoom ratio	1.6:1	Width	440 mm
Throw ratio	1.35 - 2.2:1	Depth	304 mm
Horizontal lens shift range	-20 - 20%	Height	120 mm
Vertical lens shift range	-50 - 50%	Weight *	8.5 kg
Video		Package width	538 mm
Full HD *	Image: A start of the start	Package depth	564 mm
Colour modes (2D)	Cinema, Dynamic	Package height	208 mm
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection	Package weight	11.6 kg
		Packaging content	
Ports & interfaces		Remote control included *	<ul> <li>Image: A second s</li></ul>
		Cables included	AC, VGA

Ports & interfaces		Packaging content	
USB 2.0 ports quantity USB 2.0 Type-B ports quantity Audio (L/R) in * Audio (L/R) out Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity *	1 1 1 1 RS-232 3 2	Quick start guide Manual Bundled software Logistics data	<ul> <li>EasyMP Monitor</li> </ul>
		Quantity per pack Products per pallet Pallet gross weight	1 pc(s) 14 pc(s)
Network		Pallet gross length	0 g 120 cm
Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates Wi-Fi * Wi-Fi standards Miracast	✓ 1 10,100 Mbit/s ✓ 802.11a, 802.11b, 802.11g ✓	Pallet gross width Pallet gross height Products per pallet layer Products per pallet layer (UK) Products per pallet (UK) Pallet weight (UK)	80 cm 2.18 m 2 pc(s) 2 pc(s) 14 pc(s) 0 g
Noise level * 3	27 dB 38 dB China	Pallet length (UK) Pallet width (UK) Pallet height (UK) Other features	120 cm 100 cm 2.18 m
		RS-232 ports	1



8715946661568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.