

Epson EB-L615U Standardni projektor 6000 ANSI lumena 3LCD WUXGA (1920x1200) Crno



Brand : Epson

Product code: V11H901140

Product name : EB-L615U

Epson EB-L615U. Osvetljenje projektora: 6000 ANSI lumena, Tehnologija projektovanja: 3LCD, Osnovna rezolucija projektora: WUXGA (1920x1200). Tip izvora svetlosti: Laseri, Radni vek izvora svetlosti: 20000 č, Radni vek izvora svetlosti (ekonomični režim): 30000 č. Fokus: Ručno, Opsezi fokalne dužine: 20 - 31.8 mm, Otvor blende: 1,5 - 1,7. Režimi boje (2D): Bioskopski, Dinamički, Režimi boje video-zapisa: Bioskopski, Dinamički, Prezentacije, sRGB, Režim DICOM simulacije, Multi-projection. Vrsta serijskog interfejsa: RS-232

Projector		Features	
Screen size compatibility *	1270 - 12700 mm (50 - 500")	Password protection	✓
Projection distance	1.44 - 23.84 m	Multimedia	
Projection distance (wide)	1.4 - 14.8 m	Built-in speaker(s) *	✓
Projection distance (tele)	2.4 - 23.8 m	RMS rated power	10 W
Contrast ratio (dynamic)	2500000:1	Design	
Projector brightness *	6000 ANSI lumens	Product type *	Standard throw projector
Projection technology *	3LCD	Product colour *	Black
Projector native resolution *	WUXGA (1920x1200)	Placement	Desktop
Contrast ratio (typical) *	2500000:1	Cable lock slot	✓
Native aspect ratio *	16:10	Cable lock slot type	Kensington
Number of colours	1.07 billion colours	Power	
Projector brightness (economic mode)	4200 ANSI lumens	Power consumption (typical) *	353 W
Keystone correction, horizontal	-30 - 30°	Power consumption (standby) *	0.3 W
Keystone correction, vertical	-30 - 30°	Power consumption (economy mode)	265 W
Matrix size	1.7 cm (0.67")	AC input voltage	100-240 V
Light source		AC input frequency	50 - 60 Hz
Light source type *	Laser	Software	
Service life of light source *	20000 h	Software support	via: AMX, Crestron (Network), Control4, Extron
Service life of light source (economic mode)	30000 h	Operational conditions	
Lens system		Storage temperature (T-T)	-10 - 60 °C
Focus *	Manual	Operating relative humidity (H-H)	20 - 80%
Focal length range	20 - 31.8 mm	Storage relative humidity (H-H)	10 - 90%
Aperture range (F-F)	1.5 - 1.7	Weight & dimensions	
Zoom capability	✓	Width	440 mm
Zoom type	Manual	Depth	304 mm
Zoom ratio	1.6:1	Height	120 mm
Throw ratio	1.35 - 2.2:1	Weight *	8.5 kg
Horizontal lens shift range	-20 - 20%	Package width	538 mm
Vertical lens shift range	-50 - 50%	Package depth	564 mm
Video		Package height	208 mm
Full HD *	✓	Package weight	11.6 kg
Colour modes (2D)	Cinema, Dynamic	Packaging content	
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode, Multi-projection	Remote control included *	✓
Ports & interfaces		Cables included	AC, VGA

Ports & interfaces		Packaging content	
USB 2.0 ports quantity	1	Quick start guide	✓
USB 2.0 Type-B ports quantity	1	Manual	✓
Audio (L/R) in *	1	Bundled software	EasyMP Monitor
Audio (L/R) out	1		
Serial interface type *	RS-232	Logistics data	
VGA (D-Sub) ports quantity *	3	Quantity per pack	1 pc(s)
HDMI ports quantity *	2	Products per pallet	14 pc(s)
Network		Pallet gross weight	0 g
Ethernet LAN *	✓	Pallet gross length	120 cm
Ethernet LAN (RJ-45) ports	1	Pallet gross width	80 cm
Ethernet LAN data rates	10,100 Mbit/s	Pallet gross height	2.18 m
Wi-Fi *	✓	Products per pallet layer	2 pc(s)
Wi-Fi standards	802.11a, 802.11b, 802.11g	Products per pallet layer (UK)	2 pc(s)
Miracast	✓	Products per pallet (UK)	14 pc(s)
Features		Pallet weight (UK)	0 g
Noise level (economic mode)	27 dB	Pallet length (UK)	120 cm
Noise level *	38 dB	Pallet width (UK)	100 cm
Country of origin	China	Pallet height (UK)	2.18 m
		Other features	
		RS-232 ports	1



8715946661568

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-APR-2025. Prints or copies of Information are only valid on the printed Publication date