

## Epson EB-450Wi 2500 ANSI lumens LCD WXGA (1280x800) Màu xám, Màu trắng

**Nhãn hiệu :** Epson

**Mã sản phẩm:** V11H317040ET

**Tên mẫu :** EB-450Wi

Epson EB-450Wi. Độ sáng của máy chiếu: 2500 ANSI lumens, Công nghệ máy chiếu: LCD, Độ phân giải gốc máy chiếu: WXGA (1280x800). Loại nguồn sáng: Đèn, Tuổi thọ của nguồn sáng: 2500 h, Tuổi thọ của nguồn sáng (chế độ tiết kiệm): 3500 h. Tiêu điểm: Thủ công, Tiêu cự: 0 - 4.68 mm. Loại giao diện chuỗi: RS-232. Mức độ ồn: 35 dB, Nước xuất xứ: Trung Quốc



<b>Projector</b>		<b>Multimedia</b>	
Screen size compatibility *	1498.6 - 2463.8 mm (59 - 97")	Built-in speaker(s) *	✓
Projector brightness *	2500 ANSI lumens	RMS rated power	10 W
Projection technology *	LCD	Number of built-in speakers	1
Projector native resolution *	WXGA (1280x800)	<b>Design</b>	
Contrast ratio (typical) *	2000:1	Product colour *	Grey, White
Keystone correction, horizontal	5°	<b>Power</b>	
Keystone correction, vertical	5°	Power consumption (typical) *	338 W
<b>Light source</b>		Power consumption (standby) *	9 W
Light source type *	Lamp	<b>Operational conditions</b>	
Service life of light source *	2500 h	Operating temperature (T-T)	0 - 35 °C
Service life of light source (economic mode)	3500 h	<b>Weight &amp; dimensions</b>	
Lamp type	UHE	Weight *	5.8 kg
Lamp power	230 W	Package width	580 mm
<b>Lens system</b>		Package depth	800 mm
Focus *	Manual	Package height	340 mm
Focal length range	0 - 4.68 mm	Package weight	22.6 kg
<b>Ports &amp; interfaces</b>		<b>Packaging content</b>	
S-Video inputs quantity	1	Remote control included *	✗
USB 2.0 ports quantity	1	<b>Logistics data</b>	
Headphone outputs	2	Quantity per pack	1 pc(s)
Serial interface type *	RS-232	Products per pallet	10 pc(s)
VGA (D-Sub) ports quantity *	2	Pallet gross length	120 cm
Component video (YPbPr/YCbCr) in *	2	Pallet gross width	80 cm
DVI port *	✗	Pallet gross height	185 cm
<b>Network</b>		Products per pallet layer	2 pc(s)
Ethernet LAN *	✓	Products per pallet layer (UK)	2 pc(s)

Network		Logistics data	
Ethernet LAN (RJ-45) ports	1	Products per pallet (UK)	10 pc(s)
Wi-Fi *	✘	Pallet length (UK)	120 cm
Features		Pallet width (UK)	100 cm
Noise level *	35 dB	Pallet height (UK)	185 cm
Country of origin	China	Other features	
		Aspect ratio	16:10
		Dimensions (WxDxH)	369 x 481 x 115 mm
		Power requirements	100 - 240V, 50/60Hz
		Connectivity technology	Wired
		RS-232 ports	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-APR-2025. Prints or copies of Information are only valid on the printed Publication date